



Penetrating OIL

4-IN-1 SPRAY:

- Lubricates
- Penetrates
- Displaces moisture

PLEASE USE THIS PROOF TO CHECK THE FOLLOWING:

- Spelling • Punctuation • Font Size & Style
- Graphic Placement • Final Size

Please Note: This proof is a digital file and can only be reproduced as well as your monitor or printer's capabilities and will not necessarily match the finish product.

DANGER
EXTREMELY FLAMMABLE
VAPORS HARMFUL. CONTENTS UNDER PRESSURE.

KEEP OUT OF REACH OF CHILDREN.
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.

SI USTED NO ENTIENDE LA ETIQUETA, BUSQUE A ALGUIEN
PARA QUE SE LA EXPLIQUE A USTED EN DETALLE.

(If you do not understand this label, find some-
one to explain it to you in detail.)



NET WT.: 15 OZ (425 G)

STOCK#
PO-15

PENETRATING OIL frees rusted and corroded nuts, bolts, studs, set screws, aluminum and copper fittings. Also lubricates and prevents corrosion on rusted and frozen parts. Can be used on most metal, wood and painted surfaces. Use PENETRATING OIL in garages, factories, on farm machinery, marine and aeronautical equipment, in shops and homes.

DIRECTIONS

Hold container upright 6 to 8 inches from surface to be sprayed. Spray area to be treated liberally and allow sufficient time for complete penetration. Repeat treatment on extremely corroded parts. Tapping or heating may be required in some severe instances.

PENETRATING OIL

DANGER

KEEP OUT OF REACH OF CHILDREN. READ LABEL AND SDS BEFORE USE. EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE DROWSINESS OR DIZZINESS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.



Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves. Wear eye protection.

FIRST AID

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

Manufactured for



12708 Milwaukee Ave.
LUBBOCK, TEXAS 79424

Phone: (806) 794-4505

Fax: (806) 794-5612
robbieenterprises.com

INGREDIENTS (CAS#): Aliphatic petroleum distillates (8008-20-6), Hydrotreated petroleum distillate (64742-47-8), Petroleum lube oil (64742-65-0), Propane (74-98-6), Butane (106-97-8).

HMS Ratings: Health: 2; Flammability: 4; Reactivity: 0; Maximum Personal Protection: G

VOC CATEGORY: PENETRANT/RUST CONTROL LUBRICANT

VOC CONTENTS: < 25%

MEETS THE VOC STANDARDS FOR: EPA, IL, IN, MI, OH, OTC AND CALIFORNIA.

VOC Compliant

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold "as is" and the manufacturer makes no warranty, express or implied, of merchantability, fitness for a particular purpose or otherwise.



451820P6453 040815